

TECHNICAL DATA VALIRYO 2.0

| DIMENSIONS: | | | | 29,5 cm | | | |
|---|---|--------|----------|---------|-----|-------|--------------------|
| | | | 11.61 in | | | | |
| Size: | 218 cm x 29,5 cm 85.43 in x 11.61 in | | _ | | - | | |
| Depth: | Less than 4 cm (column up to 170 cm) Less than 1.6 in (column up to 66.92 ir | | Î | | | | |
| Weight: | 9,8 Kg (5,5 casing + 4,3 column) 21.61 lbs (12.12 casing + 9.47 column) |) | | | | - | |
| Packaging: | 2,1 Kg (4.63 lbs) | | | | • • | | |
| TECHNICAL DATA: | | | | | | Ť | |
| Power: 2870 W Engine Speed: 5000 rpm | | | | | • | | |
| Voltage: 220-240 V ~50-60 Hz Intensity: 12 A | | | | | • | • | |
| Consumption: 0,143 kWh (use at maximum temperature) | | | | | • | | |
| MISCELLANEOUS: | | 218 cm | 85.43 in | | • | | |
| Material: ABS + PMMA anti-vandal Treatment: anti-bacterial with Silver Ions | | 2 | 80 | | | • 2.5 | 170 cm 66.93 in |
| No. of diffusers: 27 Air Speed: 100 km/h (62 mph) | | | | | 6 | • | 17(66 |
| Temperature of Use : 5 - 40 °C (41 - 104 °F) Heat emitted : 32 °C (89,6 °F) above ambient temperature* | | | è* | | ٠ | | |
| Recommended installation: inside the shower area Index Water Protection: IP56 | | | | | • | • | |
| | approximately 3 minutes (a modern dryer produces 85 dB) | | | | • | • | |
| *Temperature a and lower diffus | ind speed variation between upper ser: < 2 % | | _ | | | • | |